

# EE-6213/6214

龙门式双柱举升机, 手动解锁

CLEAR FLOOR LIFT, MANUAL RELEASE



## 主要特征

龙门式设计, 让车下工作更轻松;  
手动双边解锁;  
ABS控制盒, 24V电控盒和限位控制电压, 避免高压触电危险;

铝壳电机防止电机过热;

防护栏, 车门防撞垫有效预防意外损伤;

含配适合轻卡使用的高度支架;

特别的液压系统设计, 避免超载运行;

配置多功液压油阀板, 停电情况下可使用手动紧急下降电磁阀和手动泵接口使举升机安全下降;

经过115%动态负载测试, 150%静态负载测试;

符合CE标准。

## MAIN FEATURES

Clear floor design makes under-vehicle service more convenient.  
Manual mechanical lock release system.  
The 24V ABS control box and limit switch considers your safety operation.

Aluminum motor prevents overheating caused by long time working.

Feet - protection bar and door-opening protection rubber pad effectively avoid unexpected injuries and damages.

With height adapters for servicing light-duty trucks.


Over loading can be perfectly avoided due to the pre-fixed hydraulic pressure.

Reserved hand pump joint on hydraulic block for emergency lowering.

It has been proofed by dynamic test with 115% of rated capacity and static test with 150% of rated capacity.

CE Certificated.

## 外形尺寸 | OVERALL DIMENSION



## 技术参数 | TECHNICAL DATA

型号	MODEL NO.	EE-6213	EE-6214
举升重量	Lifting capacity	3200Kg	4000Kg
重量	Weight	720Kg	760Kg
举升时间	Lifting time	50S	55S
举升高度	Max lifting height	1900mm	
电机功率	Capacity of motor	2.2KW	
电源要求	Electricity supply	220V/240V/380V/415V 1/3 PHASE	
额定油压	Rated oil pressure	18Mpa	

## 细节展示 | DETAIL DISPLAY



## 选配 | OPTIONAL ACCESSORIES

快速托臂 Quick Arm

